

# SA Polycarbonate Traffic Signals

## DATA SHEET



### DESCRIPTION


The standard signal is composed of three polycarbonate LED-ready body sections containing the door and visor. The basic construction design provides minimum weight by maximum rigidity and strength. The housing, door and visor are injection molded of ultraviolet stabilized, pre-colored opaque polycarbonate. It meets or exceeds ITE specifications.



### FEATURES

- ▶ **Housing** – One piece unit with serrations in 5° increments at each end. Each housing has provisions for mounting two terminal blocks and attaching backplates. Housings may be fastened together to make multi-section signals. The 8" and 12" housings can be intermixed to form combination signals. SA polycarbonate wall thickness = .093"
- ▶ **Door** – One piece polycarbonate unit equipped with stainless steel hinge pins. Stainless steel thumbscrews are used to hold the door against the housing.
- ▶ **Visor** – The removable twist-on visor is secured to the door with stainless steel hardware. Cap, tunnel, and full circle visors are available.
- ▶ **Positive Positioning** – Positive positioning and locking is achieved through the use of serrated brackets, mast arm, or span wire fittings.
- ▶ **Terminal Block** – All terminal blocks are composed of a sturdy polycarbonate weather resistant casing and stainless steel hardware. Terminal block is standardly installed in the yellow section of signal (second from top).
- ▶ **Hardware** – Stainless steel material inside and outside.


## SIGNAL REPLACEMENT PARTS



Ref. No	Description	Part Number	
		8" (200mm)	12" (300mm)
1	Signal Housing, Green	KB19113	KB4818
	Signal Housing, Yellow	KB19111	KB8416
	Signal Housing, Black	KB19112	KB8417
2	Screw (10 - 24 hex screw)	141716	141716
3	Flange Nut	150715	150715
4	Door Hinge Pin	K1196	K1196
5	Thumbscrew, SS	141212	141212
6	Thumbscrew Washer, SS	155924	155924
7	Hole Plug	PHP16	PHP16
8	Lens Clip, Generic	A84436155	A84436155
9	Lens Clip, Screw	133029	133029
10	Signal Door, Green	PDM2029	PDM2032
	Signal Door, Yellow	PDM2028	PDM2031
	Signal Door, Black	PDM2027	PDM2030
11	Visor - Tunnel	A700119 XX	A700120 XX
	Visor - Cutaway	A700468 XX	A700469 XX
12	Visor Screw (10-32 × 3/8")	135021	135021
13	Terminal Block, 6 Pos. Spade Type	PCT100TX	PCT100TX
14	Terminal Block Screw, SS	A702121	A702121

Weights	8" (200mm)	12" (300mm)
Single Section with Visor	4 lbs (1.81 kg)	7 lbs (3.18 kg)
Housing Only	1 lbs 6.4 oz (.64 kg)	2 lbs 5.2 oz (1.05 kg)
Door Only	7.5 oz (.21 kg)	15.1 oz (.43 kg)

## 8" (200MM) SIGNAL DIMENSIONS



## 12" (300MM) SIGNAL DIMENSIONS

