SPEEDCHECK-15/18

Radar Speed Sign Data Sheet

* carmanah°

Quality radar speed sign systems packed with features to maximize effectiveness:

- ✓ Large 15" or 18" LED digits with various static sign sizes
- Optional "SLOW DOWN" message, strobes and external beacons available
- High-contrast display provides the greatest readability at a distance
- ✓ Stealth mode
- ✓ Calendar/schedule operation
- Data collection with visualization and reporting software
- ✓ 3-year warranty

Fully Compliant, Ultra-clear Display

Compliant to MUTCD standards for legibility, including LED color, character and letter height. The bright LED displays use 15-inch and 18-inch digits against a background designed for high-contrast visibility that prevents "88" ghosting—ensuring readability in all weather and lighting conditions. The unique safety mask limits the viewing angle to prevent drivers from watching the display as they pass. The "SLOW DOWN" message can be programmed to flash at user-defined speed thresholds.

Long-lasting, Reliable Operation

The LED display is housed within a durable, weatherproof aluminum unit and is shielded with a tough polycarbonate window for added vandalism protection. Every solar-powered model is solar-sized by location to ensure year-after-year operation. Carmanah includes a Solar Power Report to prove sustainability over a 12-month period.

Easy Installation and Connectivity

The modular design makes it easy to repair using standard tools—without removing the device from the pole. Bluetooth® allows for quick connectivity and setup via the SpeedCheck Manager PC software. A StreetHub™ model comes factory prewired and pretested for remote communication—enabling cloud-based access within minutes. Carmanah's comprehensive support system includes product support technologists and our 24/7 ondemand Product Support Center.



SPEEDCHECK-15

15-inch digits for speeds less than 45 mph (70 km/h)

SPEEDCHECK-18

18-inch digits for speeds equal/greater than 45 mph (70 km/h)



MUTCD compliant



Buy America compliant



3-year limited warranty



Solar-sized for every location



Up to 1000 feet radar detection


SPEEDCHECK-15/18


Radar Speed Sign Data Sheet

1.844.412.8395 | traffic@carmanah.com | carmanah.com

LED DISPLAY SPEEDCHECK-15







| LED Display | Meets MUTCD legibility standards for character height and LED color for roadways with speed limits under 45 mph and 45 mph and over |
|--------------|---|
| | Seven-segment digit design using amber LEDs |
| | LEDs automatically dim during nighttime operation, minimizing light |
| | bounce into neighboring windows |
| | Includes stealth mode for data collection |
| Radar | 3rd-party tested radar detection range to 1000 ft. |
| | Single-direction, K Band Doppler radar (+/- 1 mph) with 12° radar beam width |
| Construction | Corrosion-resistant aluminum chassis with stainless steel hardware |
| | 1/4" polycarbonate window protects digital display from weather and vandalism |
| | |

| OPTIONAL PRODUCT FEATURES | | |
|---------------------------|---|--|
| Slow Down | Flashes MUTCD-compliant "SLOW DOWN" message when drivers exceed user-defined speed thresholds; available in yellow or red* LEDs | |
| Outputs | Triggers external devices, such as flashing beacons, strobes, or cameras by speed threshold or schedule, or from centralized remote location Strobe*: rapid-flashing strobe with white LEDs or red/blue LEDs (for 15" display only) Beacons: 12" (305 mm) or 8" (203 mm) diameter LED modules, yellow or red | |

Allows external devices to manage display operation with external

Flat Bracket

LED DISPLAY MOUNTS



Inputs





| COMMUNICATION AND DATA COLLECTION | | |
|---|--|--|
| Bluetooth, direct serial (cable) and third-party device communication | | |
| options available | | |
| Optional StreetHub model includes fully integrated monitoring unit from | | |
| the factory and Glance cloud-based software for two-way communication | | |
| | | |

| INCLUDED WITH EVERT SIGN | | |
|------------------------------|--|--|
| Software | SpeedCheck Manager PC software for all setup and programming options, including calendar scheduling, data collection Traffic Analyzer software for data visualization and reporting | |
| Hardware and Installation | High-powered Bluetooth dongle for up to 50 ft range between SpeedCheck sign and PC | |
| Setup | Radar installation kit with alignment tool and foam cone | |
| Warranty | 3-year limited warranty on LED display | |
| | 1-year limited warranty on batteries | |
| Support | Carmanah's North American product support technologists available for solution building, solar sizing and troubleshooting | |
| | 24/7 access to Carmanah's online Product Support Center database | |



| "YOUR SPEED" STATIC SIGN | | |
|--------------------------|--|--|
| Sign | Meets MUTCD legibility standards for color, character and height | |
| Sheeting | 3M High Intensity Prismatic or Diamond Grade retroreflective sheeting and components | |
| Color | Available in vellow, fluorescent vellow/green, white, and orange | |

SPEEDCHECK-15









30" x 30" 42" x 30" (762 mm x 762 mm) (1067 mm x 762 mm) (1219 mm x 914 mm) (1524 mm x 1219 mm)

60" x 48'

POWER OPTIONS

| Solar | 12 VDC operation, solar-sized to specific geographic location Includes 12-month Solar Power Report to ensure system reliability | |
|-------|---|--|
| | System designed for 5+ year battery life | |
| AC | 100-240 VAC in standard configurations | |

| BATTERY AND CONTROL CABINET | | |
|-----------------------------|--|--|
| Construction | Weatherproof, gasketed cabinet with vents for ambient air transfer tested to NEMA 3R | |
| | Corrosion-resistant aluminum chassis with stainless steel hardware | |
| | Lockable, hinged door with #2 lock | |
| | Optional padlockable latch | |
| | Raw aluminum finish or yellow, black, or green powder coated | |
| Dimensions | 15.7" x 8.2" x 21.0" | |
| | (399 mm x 208 mm x 534 mm) | |

SOLAR PANELS AND MOUNTS

Top of Pole Mount





Side of Pole Mount

| PANEL | LENGTH | WIDTH |
|-------|-----------------|----------------|
| 50 W | 26.3" (668 mm) | 21.2" (538 mm) |
| 80 W | 30.7" (780 mm) | 26.5" (672 mm) |
| 170 W | 59.1" (1500 mm) | 26.3" (668 mm) |
| | | · |

LEARN MORE ABOUT THE PRODUCT

- What's a Solar Power Report?
- Visit the Product Support Center

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Carmanah Technologies is under license. Other trademarks and trade names are those of their respective owners.

Specifications subject to local environmental conditions, and may be subject to change.

All Carmanah products are manufactured in facilities that are certified to ISO quality standards. "Carmanah" and Carmanah logo are trademarks of Carmanah Technologies Corp. © 2021, Carmanah Technologies Corp.

Document: DATA_TRA_SPEEDCHECK-15-18-radar-speed-sign_RevA

contact closure and the included wiring harness * Not FHWA MUTCD compliant