Edco EMC-240B

120/240 VAC Heavy Duty (Parallel)

The Edco EMC 240B surge suppressor is designed to protect AC distribution panel circuits or 120V power supplies feeding sensitive electronic equipment. Electrically, the unit incorporates MOV and thermal fusing technology. The Edco EMC 240B is designed to be installed in parallel on standard single phase 120 VAC (L,N,G) circuits.





General Technical Specifications

Operating Voltage	120/240 VAC
Clamping Voltage	395 VAC
Operating Current	NA, Parallel
Total Peak Surge Current	80 kA (8 x 20 μs)
Operating Frequency	47-63 Hz
EMI Attenuation (100 kHz to 100 MHz)	>40 dB
SPD Technology	Metal Oxide Varistors (MOVs)
Modes of Protection	Line-to-Line Line-to-Neutral
Status Indication	Power On & MOVs functional
Connection Type	Wire Leads
Operating Temperature	-40°C to +85°C
Dimensions (Inches)	4.6H x 2.2W x 2.8L
Weight	13.5 oz
Certifications	UL 1449, Suppressor/ OWHX Arrester

Features

- Fast response time
- 40,000 Amps per phase capacity
- Failsafe and fused
- Operational status indicators
- UL 1449 listed and OWHX listed
- 5 year warranty


Caution


- Installation and service should be performed by qualified electricians only.
- 2. Before installing EMC, remove all electrical power from circuits.






Installation





Dimensions



Caution

- 1. Installation and service should be performed by qualified electricians only.
- 2. Before installing EMC, remove all electrical power from circuits.
- 3. Connect on load side of main breakers.
- 4. Preferably use 2 dedicated 30A circuit breakers.

Emerson Network Power.

AC Power The global leader in enabling Connectivity Business-Critical Continuity $^{\mathbb{M}}$. DC Power

■ Embedded Computing Embedded Power

Monitoring

Outside Plant Power Switching & Control Precision Cooling

Racks and Integrated Cabinets Services

Surge Protection

Emerson Network Power Contact information

Headquarters Surge Protection 328 Water Street Binghamton, NY 13901 T: (607) 721-8840 T: (800) 288-6169 F: (607) 722-8713 E: contactsurge@emerson.com

IO-50101 1/09 Rev. 1 Printed in USA

650 SW 27th Avenue Ocala, FL 34471 T: (352) 732-3029 T: (800) 648-4076 F: (352) 867-1237

www.emersonnetworkpower.com



Business-Critical Continuity, Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co. @2009 Emerson Electric Co.

