



Vantage Edge[®]2

A machine vision processor that delivers superior performance

Benefits of the Vantage Edge2 System



Includes SmartCycle[®] and PedTrax[™] technology



Simple to use interface reduces training time and improves productivity



Ease of set up and minimal lane closure time reduces manpower cost and keeps traffic flowing during equipment installation



State-of-the-art video detection processor

The Vantage Edge[®]2 processor is a key component in the family of Vantage[®] video detection solutions. The module combines state-of-the-art technology with sophisticated algorithms to deliver dependable vehicle detection required for today's complex transportation systems. The Edge2 processor features single or dual video inputs to maximize configuration efficiencies for intersection control, highway monitoring, and ramp metering flow control applications.

Maximum flexibility with optional modules

The processor module is complimented by multiple Input/Output and Extension Modules that provide flexible and expandable solutions to meet the needs of larger and more complex intersection configurations.

The Edge2 processor module and its associated expansion modules fit into standard detector racks to simplify installation and set up. All modules are designed as a simple and cost-effective replacement for the inductive loop amplifier module configuration.

Vantage Edge[®]2

A machine vision processor that delivers superior performance

The Edge2 processor and all of its associated modules can be completely configured by using a mouse and video monitor only, eliminating the need for expensive laptops or PDA devices.

More Benefits

- "Plug and play" operation enables use of existing detector rack
- Expandable and modular system allows for optimal configuration that helps to reduce cost while preserving room for incremental growth
- Includes PedTrax[™] for pedestrian measurement and speed

SPECIFICATIONS

Power Consumption	I2 or 24 VDC, 7W maximum <ul style="list-style-type: none">• @12VDC - 490mA• @24VDC - 280mA	Detector I/O	Outputs (open collector +24VDC nominal 50mA) <ul style="list-style-type: none">• 4 on rear edge of module
Video	Input type <ul style="list-style-type: none">• NTSC, PAL• 75 Ohm I Vpp 1 input channel <ul style="list-style-type: none">• Single BNC connector 2 input channel <ul style="list-style-type: none">• Dual BNC connector Output – All models <ul style="list-style-type: none">• Single BNC connector		Inputs <ul style="list-style-type: none">• 4 on rear edge of module
Communication Ports	USB A Mouse USB A Thumbdrive USB B Comms	Status Indicators	24 detection zones per camera channel 4 LEDs indicate output detection state 4 LEDs indicate video source
		Environmental	-35°F to +165°F (-37°C to +74°C) 0% to 95% humidity non-condensing 0.5Gm, 3 axes, 5-30Hz vibration tested 10G in all 3 axes for shock testing
		Mechanical	7" L x 4.5" H x 2.31" W. (17.78cm x 11.43cm x 5.86cm) 0.8lb (.363Kg)
		Warranty	3 years limited warranty
		Regulatory	NEMA TS-2 Compliant FCC part 15, Class A



Copyright © 2017 Iteris, Inc. All rights reserved.

NOTICE: Iteris, Inc. reserves the right to change product specifications without notice. Information furnished is for informational purposes only. This information may not be complete or the latest revision. For the most up-to-date information, please contact Iteris, Inc.

iteris[®]