



## TEMPLE EDGE-LIT™ Internally-Illuminated LED Signs

**RAZOR**  
Side Access Illuminated LED Sign



### PROVEN DESIGN

Just 1.6" deep. Weighs 5 lbs./sq. ft.

Designed to be the most durable illuminated street name sign on the market.

Slide-Lock mechanism gives the RAZOR adaptability for both single and double-sided applications while using the same sign frame.

UL Certified Class 2 Power Supplies and LEDs are fully accessible via the RAZOR's removeable end caps.

### PROVEN QUALITY

Over 6 years in production, with over 10,000 units deployed (formerly called the R409A).

Only a 0.5% failure rate (only 1 sign for every 200 shipped).

Temple ensures that each RAZOR sign is built to very rigorous quality standards and tested for 24 hours prior to shipment.

### PROVEN PERFORMANCE

The RAZOR uses high-intensity LEDs rated for 60,000 hours-- over 14 years of maintenance-free illumination!

RAZOR's state-of-the-art LEDs are integrated into a rugged, thermally-designed circuit board that provides even illumination throughout the entire sign.

Meets or exceeds all industry standards for lux measurements.

[www.TempleEdgeLit.com](http://www.TempleEdgeLit.com)  
800.633.3221

Temple Edge-Lit™ is a Division of Temple, Inc. © Copyright 2011. All rights reserved.

Integrity Service Relationships



QUALITYWORKS.





## TEMPLE EDGE-LIT

Internally-Illuminated LED Signs



### RAZOR

### RAZOR. Priority Regulatory Signs

#### COMMON SPECIFICATIONS

Internally-Illuminated LED Street Name Signs

Internally-Illuminated LED Regulatory Signs

#### MECHANICAL

#### MECHANICAL

Dimensions:	Length	24" to 120" at 6" increments
	Height	15", 18", 20", 22", 24", 30"
Thickness		1.6"

Dimensions:	Length	MUTCD standard sizes from 18" to 36" (width)
	Height	18H" to 36H" Max
Thickness		1.6"

#### MATERIAL

Frame 6000 Series Aluminum housing

6000 Series Aluminum housing

#### SIGN SHEETING

Optional Sheeting ASTM Type IX Retroreflective Sheeting (sign legend and background)

ASTM Type IX Retroreflective Sheeting (sign legend and background)

#### ILLUMINATION

Contrast Ratio Legend / Background contrast ratio 4:1 minimum

Legend / Background contrast ratio 4:1 minimum

#### FONTS

Default MUTCD Clearview Font, HWY E Series B, C, D, E Modified, Custom fonts available

MUTCD Clearview Font, HWY E Series B, C, D, E Modified, with Custom fonts available

#### ENVIRONMENTAL

Wind Load 150 mph (241 km/h) with 1.14 gust factor and ice loading as per AASHTO LTS-4 2001

150 mph (241 km/h) with 1.14 gust factor and ice loading as per AASHTO LTS-4 2001

#### Electrical Certification

Listed to UL48

Listed to UL48

#### MOUNTING OPTIONS

Under-hang Mount Accepts Pelco SE-5015 or SE-5146

Accepts Pelco SE-5015 or SE-5146

Single-sided Fixed Mount Accepts Pelco Astro-brac AS-3009 or equivalent

Accepts Pelco Astro-brac AS-3009 or equivalent

#### SIGN SHEETING

3M™ Electrocut™ film Yellow, Orange, Green, Black (Opaque), Red, Blue, Brown, and Clear 3M ScotchCal

Yellow, Orange, Green, Black (Opaque), Red, Blue, Brown, and Clear 3M ScotchCal

#### WEIGHT

Maximum of 7 lbs. per sq. ft., single and double-sided

Maximum of 7 lbs. per sq. ft., single or double-sided



©2011, Temple, Inc. All rights reserved.

Integrity  
Service  
Relationships



Adrian Baker  
Temple Edge-Lit Accounts Manager  
adrian.baker@temple-inc.com  
256.318.7549 (mobile voice & text)

800.633.3221 toll free  
256.353.4578 (fax)  
www.TempleEdgeLit.com