

UNIFORM APPEARANCE HAND and PERSON PEDESTRIAN SIGNALS



- ▲ **Fully compliant to ITE PTCSI Part 2 LED Pedestrian Traffic Signal Module Specification adopted 3/9/04
- ▲ Meets / exceeds ITE uniformity ratio of not more than 1 to 5 between the max and min luminance values as measured in (.5") dia spots
- ▲ Meets or exceeds ITE moisture resistance testing per MIL-STD-810F, method 506.4, I for rain & blowing rain
- ▲ Fuse and transient suppressor incorporated for superior line and load protection
- ▲ Modules fully meet maintained luminous requirements of the ITE Specification sections (6.4.4 - 6.4.4.3.1)
- ▲ Fully meets ITE chromaticity and color uniformity specifications (6.4.4.4 - 6.4.4.6)
- ▲ Independent dedicated power supplies
- ▲ 3rd party qualification testing

Part Number	Size	Description	Typical Wattage @ 25°C		Min. Luminance (cd/m²)		**Meets ITE Spec	*CSA Approved
			Hand	Person	Hand	Person		
430-6450-001X	16 x 18	Side-by-side Hand and Person	8	7	1,400	2,200	✓	✓
430-6472-001X	16 x 18	Overlay Hand and Person	8	6	1,400	2,200	✓	✓
430-5770-001X	12 x 12	Hand only	8	N/A	1,400	N/A	✓	✓
430-7771-001X	12 x 12	Person only	N/A	7	N/A	2,200	✓	✓
430-6772-001X	12 x 12	Overlay Hand and Person	8	6	1,400	2,200	✓	✓
430-5570-001X	9 x 9	Hand only	6	N/A	1,400	N/A	✓	
430-7570-001X	9 x 9	Person only	N/A	6	N/A	2,200	✓	

UNIFORM APPEARANCE COUNTDOWN PEDESTRIAN SIGNALS



- ▲ **Uniform appearance hand and man symbols fully compliant to ITE PTCSI Part 2 LED Pedestrian Traffic Signal Module Specification adopted 3/19/04
- ▲ 9" high countdown digits are MUTCD compliant for crosswalks over 100 ft
- ▲ Standard part numbers below comply with MUTCD recommendations to countdown clearance interval only
- ▲ Full preemption compatibility
- ▲ Up to 4 units can be connected in parallel without affecting of the monitoring of the Hand/Person
- ▲ Meets or exceeds ITE moisture resistance testing per MIL-STD-810F, method 506.4, I for rain & blowing rain
- ▲ Independent dedicated power supplies
- ▲ 3rd party qualification testing

Part Number	Housing Size	Symbol Color			Typical Wattage @ 25°C			Min. Luminance (cd/m2)			**Meets ITE Spec	Note
		Countdown	Hand	Person	Countdown	Hand	Person	Countdown	Hand	Person		
430-6479-001X	16 x 18	Portland Orange	Portland Orange	Lunar White	8	11	10	1,400	1,400	2,200	✓	*
430-7773-001X	12 x 12	Portland Orange	N/A	N/A	8	N/A	N/A	1,400	N/A	N/A	N/A	

Special Applications: Upon customer request, above units are available with option to countdown the clearance mode and the walk mode. Add suffix "W" to above part numbers.

IMPORTANT NOTE: MUTCD DOES NOT recommend the use of a countdown timer in the "walk" mode

* Effective 12/20/10 - New one piece housing design. Improved optical design to provide superior uniform appearance of the icons in the on state. Reduced icon off state visibility in compliance with the latest ITE specification requirements.