

Supplied by:

**mobotrex<sup>®</sup>**  
MOBILITY & TRAFFIC EXPERTS  
(800) 888-7078    **MoboTrex.com**

# 8A31DT

## SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	110Ah
Capacity at C/20	105Ah
Capacity at C/5	86Ah
Weight	69 lbs. (31 kg)
Plate Alloy	Lead Calcium
Posts	Forged Terminals & Bushings
Container/Cover	Polypropylene
Operating Temperature Range	-40°F (-40°C) - 140°F (60°C)
Charge Voltage @ 77°F (25°C)	
Charge / Absorption / Equalize	2.30 - 2.43 VPC
Float / Standby	2.23 - 2.26 VPC
Vent	Self-sealing
Terminal	S/X (SAE/STUD)



Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A. by East Penn Manufacturing Co., Inc.

Distributed by:

## Valve-Regulated, Absorbed Glass Mat Technology




## DIMENSIONS

*Inches (mm)*

Length	12.93 (328 mm)
Width	6.75 (171 mm)
Height	9.34 (237 mm) <i>including terminal</i>

**AGM Cycle Life vs Depth of Discharge at +25°C (77°F)**  
Based on BCI 2-hour Capacity



**MK Battery**

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: [sales@mkbattery.com](mailto:sales@mkbattery.com)

